



Performance Specialties

Fuel Additive ECOHEAT

ECOHEAT is a multifunctional home heating fuel additive designed to enhance a wide spectrum of performance properties.

Innospec Fuel Specialties is the only manufacturing company solely focused on fuel and fuel additive technology.

**Petroleum Products Corp.
(717) 939-0466**



Addition

ECOHEAT may be batch blended into home heating fuel. Verify that the additive is completely dissolved into the fuel.

40CFR80.591 Compliance Statement:

This additive is for non-road use only.

In order to comply with EU regulations (Title II, Chapter 1, Article 8) and to secure documentation to allow this product to be imported into the EU please contact Innospec to join our "Only Representative" and Declaration of Conformity Program.

ECOHEAT provides the following in home heating fuel:

- Lowers Pour Point
- Lowers Cold Filter Plugging Point
- Disperses wax to help prevent gelling in low temperatures
- Cleans fuel system by removing and dispersing existing sludge, allowing it to pass harmlessly through screens and filters
- Cleans burner nozzles for increased performance and efficiency
- Protects all metallic components
- Prevents catalytic degradation of the fuel induced by free metals, including copper
- Reduces opportunity for microbial growth and water-related corrosion through gradual water control
- Contains antioxidants to protect thermal and oxidative stability
- Defoamer for quicker fuel tank filling

Personal Safety, First Aid, Storage and Handling

See the Material Safety Data Sheet for product specific information.



Typical Properties

| | |
|---|--------------|
| Appearance | amber liquid |
| Specific Gravity, 60/60°F (15.6/15.6°C) | 0.906 |
| Density, lb./gal, 60°F, (15.6°C) | 7.54 |
| Flash Point, PMCC, °F (°C) | 155 (68.3) |
| Pour Point, °F (°C) | -11.2 (-24) |
| Viscosity, cSt @ 100°F (37.8°C) | 5 |
| 68°F (20°C) | 10 |
| 32°F (0°C) | 24 |
| 0°F (-17.8°C) | 75 |

Recommended Treat Rate

32 ounces : 250 gallons
For extreme cold conditions, use 32 ounces : 125 gallons

Technical Support: (302) 454-8100
Customer Service (800) 441-9547
Resource Center:



ECOHEAT 32 oz. Bottle
Edition gg1
Issue 2
5/2011 CCK